

SC4000

Wireless Data Communications by

U.L. Listed, Full Data Transfer

The SC4000 is the premier product for two-way, wireless transfer of complete alarm data. The SC4000 is U.L. listed for AA Burglary and NFPA 72 Fire reporting by radio only. The SC4000 is ideally suited for your High-End Accounts.

Using Safecom's patented digital dialer interface, the SC4000 captures all of the alarm data that would normally be sent via a telephone line and sends it, via two-way radio, to the central monitoring station. The SC4000 has also been designed with 4 inputs and 4 output relays to provide remote radio control of critical functions.

The two-way communications capability in every Safecom product means that individual units can be remotely controlled and supervised. All of the radio control parameters and supervision timing intervals can be programmed directly from the central monitoring station. Safecom has taken care to design a quality product that is easily installed and that will provide fast and reliable communications.



PRODUCT SPECIFICATIONS

General	Size	11.25"W x 11.25"H x 3.5"
	Weight	8 lbs
	Temperature-Operating	0° C to + 60° C
	Storage	-40° C to +75° C
	Operating Voltage	120/240 VAC, 60/65 Hz
	Optional Battery/ Backup Time	12 VDC/7Ah/24 Hr.
	Panel Indicators	AC Power/Panel Trouble
	Panel Control	Buzzer Silence
	Panel Door Monitor	Box Tamper Switch
	Connections	4 Inputs, 4 Outputs, 18 VAC
	Supported Formats	Radionics Modem II & IIe All Ademco DTMF Radionics BFSK FBI Super Fast, & SIA-R All 3x1 and 4x2 Pulsed

FEATURES

- U.L. Listed
- Full Data Transfer
- Remotely Programmable
Supervision and Polling
- 4 Inputs and 4 Output Relays
- Includes Antenna

